






項次	名 稱	料 號	材 質	電鍍或顏色	數量	備註
1	母膠心	UA0017000	NYLON66,UL 94 V-0	BEIGE	1	
2	本體護蓋	UA00570XX	BRASS,T=0.40±0.03MM	TIN OR NICKEL PLATED	1	
3	焊線端子	UA00340XX	PHOSPHOR BRONZE T=0.25±0.03MM	SEE TABLE	4	
4	母座-後塞	UA0018000-1	PBT+15%GF,UL 94 V-0	BLACK OR WHITE OR BEIGE	1	△B ₀

ELECTRICAL CHARACTERISTICS:
 RATING:30V DC/AC 1A Max.
 CONTACT RESISTANCE:30mΩ Max.
 INSULATION RESISTANCE:100MΩ Min.at 500V DC.
 DIELECTRIC STRENGTH:750V AC/1 minute.
 INSERTION FORCE: 3.6kgf MAX
 WITHDRAWAL FORCE: 1.0kgf MIN

TABLE:

XX	電 鍍
11	G.F./TIN PLATED前金後錫
12	3U" G./TIN PLATED前金後錫
13	5U" G./TIN PLATED前金後錫
14	10u" G./TIN PLATED前金後錫
15	15U" G./TIN PLATED前金後錫
16	20U" G./TIN PLATED前金後錫
17	30U" G./TIN PLATED前金後錫
18	50U" G./TIN PLATED前金後錫



東莞世華電子有限公司

SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)

地址:東莞市塘廈鎮諸佛嶺178工業區

TEL:0769-7910020-1 FAX:0769-7910210

DRAWN BY

CHECKED BY

APPROVED BY

ITEM

PART NO

USB CONNECTOR(series A)

-母座(有腳180°)

UA09200XX

ANGLE PROJECTION



X.XX±0.20

UNIT

SCALE

DATE

MM

4:1

04/07/2003



REVISION

材質變更,舊圖作廢

DESCRIPTION

04/07/2003

DATE