



BOM:

項次	名稱	料號	材質	電鍍或顏色	數量	備註
1	母膠心	DP0900003-1	High-temperature plastics	BLUE(PANTONE 300C)	1	
2	外殼	DP0900003-2	BRASS T=0.40MM	NICKEL PLATED	1	
3	後塞	DP0900003-3	High-temperature plastics	BLUE(PANTONE 300C)	1	
4	PIN A	DP0900003-5XX	BRASS T=0.25MM	SEE TABLE1	5	
5	PIN B	DP0900003-6XX	PHOSPHOR BRONZE T=0.25MM	SEE TABLE1	4	
6	後蓋	DP0900003-4	SPCC T=0.30MM	NICKEL PLATED	1	

ELECTRICAL CHARACTERISTICS:
 30V DC/AC 1A Max.
CONTACT RESISTANCE: 30mΩ Max.
INSULATION RESISTANCE:
 100MΩ Min.at 500V DC.
DIELECTRIC STRENGTH:
 750V AC/1 minute.
INSERTION FORCE: 3.6kgf MAX
WITHDRAWAL FORCE: 1.0kgf MIN

TABLE1:

XX	PLATED
11	G.F./TIN PLATED前金後錫
12	3U"G./TIN PLATED前金後錫
13	5U"G./TIN PLATED前金後錫
14	10u"G./TIN PLATED前金後錫
15	15U"G./TIN PLATED前金後錫
16	20U"G./TIN PLATED前金後錫
17	30U"G./TIN PLATED前金後錫
18	50U"G./TIN PLATED前金後錫

東莞世華電子有限公司
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)
 地址:東莞市塘廈鎮諸佛嶺178工業區
 TEL:0769-7910020-1 FAX:0769-7910210

DRAWN BY	陳長江	ITEM	USB-A(3.0版)母座(DIP)		ANGLE PROJECTION	UNIT	mm	修訂圖面 與實物一致	02/25/2010
CHECKED BY			PART NO	DP0900003-XX	TOLERANCE	.X±0.2 .XX±0.10	SCALE		
APPROVED BY					DATE	02/25/2010	REVISION	DESCRIPTION	DATE