

SECTION A-A  
SCALE 1:1

BOM:



項次	名稱	料號	材質	電鍍或顏色	數量	備註
1	後塞	DP0900006-1	High-temperature plastics	BLUE(PANTONE 300C)	1	
2	母膠心	DP0900006-2	High-temperature plastics	BLUE(PANTONE 300C)	1	
3	PIN A	DP0900006-1XX	PHOSPHOR BRONZE T=0.25MM	SEE TABLE1	4	
4	PIN B	DP0900006-2XX	BRASS T=0.25MM	SEE TABLE1	5	
5	外殼	DP0900006-3	BRASS T=0.40MM	TIN OR NICKEL PLATED	1	

ELECTRICAL CHARACTERISTICS:  
 30V DC/AC 1A Max.  
 CONTACT RESISTANCE: 30mΩ Max.  
 INSULATION RESISTANCE:  
 100MΩ Min.at 500V DC.  
 DIELECTRIC STRENGTH:  
 750V AC/1 minute.  
 INSERTION FORCE: 3.6kgf MAX  
 WITHDRAWAL FORCE: 1.0kgf MIN

TABLE1:

XX	PLATED
11	G. F. /TIN PLATED前金後錫
12	3U"G. /TIN PLATED前金後錫
13	5U"G. /TIN PLATED前金後錫
14	10u"G. /TIN PLATED前金後錫
15	15U"G. /TIN PLATED前金後錫
16	20U"G. /TIN PLATED前金後錫
17	30U"G. /TIN PLATED前金後錫
18	50U"G. /TIN PLATED前金後錫

 **東莞世華電子有限公司**  
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)  
 地址: 東莞市塘廈鎮諸佛嶺178工業區  
 TEL: 0769-87910020-1 FAX: 0769-87910210

DRAWN BY	陳長江	ITEM	USB-A(3.0版) 母座(180°)		ANGLE PROJECTION	UNIT	mm			
CHECKED BY		PART NO	DP0900006-XX	TOLERANCE		SCALE	1:1		設計變更 兩彈片處加寬	11/26/2009
APPROVED BY					.X±0.2 .XX±0.10	DATE	11/26/2009	REVISION	DESCRIPTION	DATE