



TABLE-2:

Y	外殼電鍍
1	吃錫鍍
2	一般金
3	2U" 金
4	3u" 金

Build of material:

8	USB3.0-A公頭(mold)-分線排(30AWG)	DP0900012-2	1	PA46, UL 94V-0;	藍色	
7	USB3.0-A公頭(mold)-分線排(28AWG)	DP0900012-1	1	PA46, UL 94V-0;	藍色	
6	USB3.0-A公頭-外殼	DP0900001-7Y	1	SPCC T=0.30mm	SEE TABLE-2	
5	USB3.0-A公頭-馬口鐵	DP0900001-6Y	1	SPCC T=0.30mm	SEE TABLE-2	
4		上座	DP0900011-4XX	1	PA46, UL 94V-0;	藍色
3		下座	DP0900011-3XX	1	PA46, UL 94V-0;	藍色
2	USB3.0-A公頭(mold)-單件式	短端子	DP0900011-2XX	5	磷銅 T=0.25mm	SEE TABLE-1
1		長端子	DP0900011-1XX	4	黃銅 T=0.25mm	SEE TABLE-1
項次	品名	料號	數量	規格	備注	

ELECTRICAL CHARACTERISTICS:
 30V DC/AC 1A Max.
 CONTACT RESISTANCE:30mΩ Max.
 INSULATION RESISTANCE:
 100MΩ Min.at 500V DC.
 DIELECTRIC STRENGTH:
 750V AC/1 minute.
 INSERTION FORCE:3.6kgf MAX
 WITHDRAWAL:1.0kgf MIN

TABLE-1:

XX	電鍍
01	前金后錫
02	3u" 前金后錫
03	5u" 前金后錫
04	15u" 前金后錫
05	20u" 前金后錫
06	30u" 前金后錫

 東莞世華電子有限公司 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN) 地址:東莞市塘廈鎮諸佛嶺178工業區 TEL:0769-87910020-1 FAX:0769-87910210	DRAWN BY	張黎林	ITEM	USB3.0-A公頭(mold)		ANGLE PROJECTION	UNIT	mm	 修改圖面	07/27/2011	
	CHECKED BY			+分線排		 SCALE	1:1	 REVISION			DESCRIPTION
	APPROVED BY			PART NO	DP0900012-XXY	TOLERANCE	.X±0.30 .XX±0.20	DATE			07/27/2011