



ELECTRICAL CHARACTERISTICS:
 RATING: 100V AC 1A MAX
 or 12V DC 2A MAX
 INSULATION RESISTANCE:
 50MΩ MIN at 250V DC
 CONTACT RESISTANCE:
 30mΩ MAX
 DIELECTRIC STRENGTH:
 250V AC/1 minute

Mechanical characteristics:
 Insertion Force :4.5kgf MAX.
 Withdrawal Force: 4.0kgf MAX, 0.9kgf MIN.
 Cycle life: 2000 times MIN.

2	接地環銅管 (一體式)	FT0809101	1	BRASS, T=0.40±0.03mm NICKEL PLATED	
1	6P 菱形母膠心 (台階5.2L)	FE0206001	1	PBT+15%GF, UL 94 V-0. BLACK.	
項次	名稱	料號	數量	規格	備註

東莞世華電子有限公司
 SHYH HWA ELECTRONICS CO., LTD. (DONGGUAN)
 地址: 東莞市塘廈鎮諸佛嶺178工業區
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY		ITEM	6P 菱形母頭(一體式) (半成品)		ANGLE PROJECTION	UNIT	MM				
CHECKED BY						SCALE	2.5:1				
APPROVED BY		PART NO	FN00605XX-FA	TOLERANCE	X.XX±0.20	DATE	07/11/2002	REVISION		DESCRIPTION	DATE