



3	SHELL	1	BRASS, T=0.40±0.03MM NICKEL PLATED OR GOLD FLASH PLATED	
2	INSULATOR	1	PBT+15%GF,UL 94 V-0	
1	SOCKET CONTACT	10	PHOSPHOR BRONZE,T=0.20±0.03MM PLATING: SEE TABLE	
項次	名稱	數量	規格	備注

ELECTRICAL CHARACTERISTICS:
 RATING: 100V AV 1A MAX or
 12V DC 2A MAX
 INSULATION RESISTANCE:
 50mΩ MIN at 250V DC
 DIELECTRIC STRENGTH:
 250V AC/1 minute

TABLE:

XX	PLATING	06	GOLD PLATED 10u" MIN.
00	NICKEL PLATED.	07	GOLD PLATED 15u" MIN.
01	TIN PLATED.	08	GOLD PLATED 20u" MIN.
02	SILVER PLATED.	09	GOLD PLATED 30u" MIN.
03	GOLD FLASH PLATED.	10	GOLD PLATED 50u" MIN.
04	GOLD PLATED 3u" MIN.	11	G.F/TIN PLATED前金后錫.
05	GOLD PLATED 5u" MIN.	12	3U"G./TIN PLATED前金后錫.

東莞世華電子有限公司
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)
 地址: 東莞市塘廈鎮諸佛嶺178工業區
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY		ITEM	10P D形杯口母頭 (15.7*17.2L)		ANGLE PROJECTION	UNIT	MM			
CHECKED BY		PART NO	FDO1003XX-DA	TOLERANCE		SCALE	5:1			
APPROVED BY		DATE	09/28/2001	REVISION		DESCRIPTION		DATE		