



3	SHELL	1	FT0010101	BRASS, t=0.40±0.03MM. NICKEL PLATED.	
2	INSULATOR	1	FE0009001	PBT+15%GF, UL 94 V-0	
1	SOCKET CONTACT	9	PI30140XX	PHOSPHOR BRONZE PLATING: SEE TABLE	
項次	名稱	數量	料號	規格	備註

ELECTRICAL CHARACTERISTICS:  
 RATING: 100V AC 1A MAX or  
 12V DC 2A MAX  
 INSULATION RESISTANCE:  
 50mΩ MIN at 250V DC  
 DIELECTRIC STRENGTH:  
 250V AC/1 minute

XX	PLATING	08	GOLD PLATED 20u" MIN.
00	NICKEL PLATED.	09	GOLD PLATED 30u" MIN.
01	TIN PLATED.	10	GOLD PLATED 50u" MIN.
02	SILVER PLATED.	11	G.F./TIN PLATED 前金後鍍.
03	GOLD FLASH PLATED.	12	3U"G./TIN PLATED 前金後鍍.
04	GOLD PLATED 3u" MIN.	13	5U"G./TIN PLATED 前金後鍍.
05	GOLD PLATED 5u" MIN.	14	10U"G./TIN PLATED 前金後鍍.
06	GOLD PLATED 10u" MIN.	15	15U"G./TIN PLATED 前金後鍍.
07	GOLD PLATED 15u" MIN.	16	20U"G./TIN PLATED 前金後鍍.

**東莞世華電子有限公司**  
 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)  
 地址: 東莞市塘廈鎮諸佛嶺178工業區  
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY		ITEM	9P杯口母頭 (15.71)		ANGLE PROJECTION	UNIT	MM	$\triangle$	工程變更, 舊圖作廢	11/20/1998
CHECKED BY					$\oplus$	SCALE	4: 1	$\triangle$	修改尺寸標注, 舊圖作廢	04/20/1998
APPROVED BY		PART NO	FD00901XX-D	TOLERANCE	X.XX±0.20	DATE	08/08/2001	REVISION	DESCRIPTION	DATE