

〈 焊線面〉

BOM

3	12.2L二粗一細四粗銅管	1	BRASS, T=0.40±0.03MM NICKEL OR GOLD FLASH PLATED.	
2	膠心	1	PBT+30%GF, UL 94V-0	
1	PIN(φ1.5*12.4L)	4	BRASS FINISH: SEE TABLE	
項次	品名	數量	規格	備注


SPECIFICATIONS:

1. Rating: PIN : DC 20V 7.5A Max.
2. Contact: resistance: 30mΩ Max.
3. Insulation Resistance: DC 250V 50MΩ Min.
4. Voltage Withstanding: AC 250V 1Minute.
5. Applicable Wire Size: AWG #18 Max.

TABLE

XX	PLATING	05	GOLD PLATED 5u" MIN.
00	NICKEL PLATED	06	GOLD PLATED 10u" MIN.
01	TIN PLATED	07	GOLD PLATED 15u" MIN.
02	SILVER	08	GOLD PLATED 20u" MIN.
03	GOLD FLASH PLATED	09	GOLD PLATED 30u" MIN.
04	GOLD PLATED 3u" MIN	10	GOLD PLATED 50u" MIN.


東莞世華電子有限公司
 SHYH HWA ELECTRONICS CO., LTD.(DONGGUAN)
 地址: 東莞市塘廈鎮諸佛嶺178工業區
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY	張敏華	ITEM	四粗公頭 (12.2L二粗一細 四粗銅管)		ANGLE PROJECTION	UNIT	MM		
CHECKED BY		PART NO	HM04006XX-□V	TOLERANCE	X.XX±0.20	SCALE	5:1		圖面修正, 舊圖作廢 04/12/2003
APPROVED BY		DATE	04/12/2003	REVISION		DESCRIPTION		DATE	