


3	3-8P 0.7T母銅管	1	FT0609101	BRASS, T=0.70±0.05MM NICKEL PLATED OR GOLD FLASH PLATED	
2	6P 母膠心	1	FE0006001	PBT+15%GF, UL 94 V-0	
1	14.0L 母PIN	6	PI30140XX	PHOSPHOR BRONZE, T=0.20±0.03MM PLATING: SEE TABLE	
項次	名稱	數量	料號	規格	備註

ELECTRICAL CHARACTERISTICS:
 RATING: 100V AC 1A MAX or
 12V DC 2A MAX
 INSULATION RESISTANCE:
 50mΩ MIN at 250V DC
 DIELECTRIC STRENGTH:
 250V AC/1 minute

TABLE:

XX	PLATING	05	GOLD PLATED 5u" MIN.
00	NICKEL PLATED .	06	GOLD PLATED 10u" MIN.
01	TIN PLATED .	07	GOLD PLATED 15u" MIN.
02	SILVER PLATED .	08	GOLD PLATED 20u" MIN.
03	GOLD FLASH PLATED .	09	GOLD PLATED 30u" MIN.
04	GOLD PLATED 3u" MIN.	10	GOLD PLATED 50u" MIN.

 **東莞世華電子有限公司**
 SHYH HWA ELECTRONICS CO., LTD.(DONGGUAN)
 地址: 東莞市塘廈鎮諸佛嶺178工業區
 TEL: 0769-7910020-1 FAX: 0769-7910210

DRAWN BY		ITEM	6P母頭 (0.7T 15.7L)		ANGLE PROJECTION	UNIT	MM			
CHECKED BY			PART NO	FK00601XX	TOLERANCE	X.XX±0.20	DATE	09/29/2001	REVISION	
APPROVED BY						SCALE	5:1		DESCRIPTION	DATE