



|    |           |                        |    |  |    |
|----|-----------|------------------------|----|--|----|
| 3  | 3-8P凸溝母銅管 | FT0109101<br>FT0109103 | 1  | BRASS, T=0.40±0.03MM<br>NICKEL PLATED OR GOLD FLASH PLATED |    |
| 2  | 4P母膠心     | FE0004001              | 1  | PBT+15%GF, UL 94 V-0                                       |    |
| 1  | 14.0L母PIN | PI30140XX              | 4  | PHOSPHOR BRONZE, T=0.20±0.03MM<br>PLATING:SEE TABLE        |    |
| 項次 | 名稱        | 料號                     | 數量 | 規格   | 備註 |

ELECTRICAL CHARACTERISTICS:  
 RATING:100V AC 1A MAX or  
 12V DC 2A MAX  
 INSULATION RESISTANCE:  
 50MΩ MIN at 250V DC  
 DIELECTRIC STRENGTH:  
 250V AC/1 minute

TABLE:

|    |                      |    |                       |
|----|----------------------|----|-----------------------|
| XX | PLATING              | 05 | GOLD PLATED 5u" MIN.  |
| 00 | NICKEL PLATED.       | 06 | GOLD PLATED 10u" MIN. |
| 01 | TIN PLATED.          | 07 | GOLD PLATED 15u" MIN. |
| 02 | SILVER PLATED.       | 08 | GOLD PLATED 20u" MIN. |
| 03 | GOLD FLASH PLATED.   | 09 | GOLD PLATED 30u" MIN. |
| 04 | GOLD PLATED 3u" MIN. | 10 | GOLD PLATED 50u" MIN. |

|  |             |     |      |         |           |                  |                    |          |           |            |             |
|--|-------------|-----|------|---------|-----------|------------------|--------------------|----------|-----------|------------|-------------|
| <br>東莞世華電子有限公司<br>SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)<br>地址:東莞市塘廈鎮諸佛嶺178工業區<br>TEL:0769-7910020-1 FAX:0769-7910210 | DRAWN BY    | 張敏華 | ITEM | 4P凸溝母頭  |           | ANGLE PROJECTION | UNIT               | MM       | 公差變更,舊圖作廢 | 06/18/2003 |             |
|  | CHECKED BY  |     |      | (15.7L) |           | SCALE            | 5:1                | REVISION |           |            | DESCRIPTION |
|  | APPROVED BY |     |      | PART NO | FX00401XX | TOLERANCE        | .X±0.2<br>.XX±0.10 | DATE     |           |            | 06/18/2003  |