



SEC A-A
SCALE 1:1

TABLE:

XX	PLATING
11	G.F./TIN PLATED 前金後錫
12	3U"G./TIN PLATED 前金後錫
13	5U"G./TIN PLATED 前金後錫
14	10U"G./TIN PLATED 前金後錫
15	15U"G./TIN PLATED 前金後錫
16	20U"G./TIN PLATED 前金後錫
17	30U"G./TIN PLATED 前金後錫
18	50U"G./TIN PLATED 前金後錫

Specification:

- Electrical Characteristics:
Voltage Current rating:1.5AMP
Dielectric Withstanding Voltage:500V AC 1min
Insulation Resistance:100MΩ min
Contact Resistance:40mΩ max
- Environmental
Operating Temperature:-20°C to 85°C

Build of material:

項次	名稱	數量	料號	材質	電鍍(或顏色)	備注
2	7P S-ATA公頭鉚線式-膠心	1	/	PBT+30%, UL 94 V-0	黑色	
1	7P S-ATA公頭鉚線式-PIN	7	/	PHOSPHOR BRONZE T=0.6±0.03mm	SEE TABLE	

 東莞世華電子有限公司 SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN) 地址:東莞市塘廈鎮諸佛嶺178工業區 TEL:0769-7910020-1 FAX:0769-7910210	DRAWN BY	鐘 杭	ITEM	7P S-ATA公頭鉚線式		ANGLE PROJECTION	UNIT	MM		
	CHECKED BY					SCALE	1:1		增加電鍍表	01/18/2008
	APPROVED BY		PART NO	CD000962007-XX-WL181	TOLERANCE	X.XX±0.20	DATE	01/18/2008	REVISION	DESCRIPTION

由 AUTODESK 教育產品製造

由 AUTODESK 教育產品製造