



SPECIFICATIONS:

1.ELECTRICAL:

INSULATION RESISTANCE: 100M Ω Min(CONDUCT TEXT INSTRUMENT)
OR 1000M Ω Min(INSULATION IMPEDANCE INSTRUMENT)

CONTACT RESISTANCE: 20m Ω Max.

DIELECTRIC WITHSTANDING VOLTAGE: 500V AC/1 MINUTE.

2.MECHANICAL:

WITHDRAWAL FORCE: 2.7Kgf(Min).

3.ENVIRONMENTAL:

OPERATING TEMPERATURE: -40°C TO +85°C.

4.Au 5u" min ;Ni 50u" min ;Sn 50u" min.

Build of materail:

3	線端母座(FDAC-U-30P)-端子	30	DP030952003-3	PHOSPHOR BRONZE(C5191R-H) T=0.15±0.02mm	5u" GOLD/50u" TIN PLATED	
2	線端母座(FDAC-U-30P)-膠心	1	DP030952003-2	PA46+30%GF, UL94 V-0	WHITE	
1	線端母座(FDAC-U-30P)-外殼	1	DP030952003-1	SUS301(1/2H), T=0.15mm±0.02mm		
項次	名稱	數量	料號	材質	電鍍(或顏色)	備註

東莞世華電子有限公司
SHYH HWA ELECTRONICS CO.,LTD.(DONGGUAN)
地址:東莞市塘廈鎮諸佛嶺178工業區
TEL:0769-7910020-1 FAX:0769-7910210

DRAWN BY	劉奎	ITEM
CHECKED BY		
APPROVED BY		PART NO

FFC線端母座
(FDAC-U-30P)
DP030952003

ANGLE PROJECTION	UNIT	MM		
	SCALE	5:1		新訂圖面
TOLERANCE	DATE	02/20/2006	REVISION	DESCRIPTION
.X±0.2 .XX±0.10	DATE	02/20/2006	REVISION	DATE